

SECTION 1) IDENTIFICATION

Product ID: Tenon Super Clear Coat - Matte

Product Name: Matte concrete coating

Revision Date: Apr 11, 2024 **Date Printed:** May 02, 2025

Version: 2.0 **Supersedes Date:** Apr 11, 2024

Manufacturer's Name: TCC Materials

Address: 2025 Centre Pointe Blvd, Mendota Heights, MN, US, 55120

Emergency Phone: 651-688-9116

Information Phone Number: 651-905-8137

Fax:

Product/Recommended Uses:

SECTION 2) HAZARDS IDENTIFICATION

Classification

Flammable Liquids - Category 3

Acute toxicity Inhalation Vapor - Category 4

Aspiration Hazard - Category 1

Carcinogenicity - Category 2

Eye Irritation - Category 2A

Reproductive Toxicity - Category 2

Skin Irritation - Category 2

Specific Target Organ Toxicity - Repeated Exposure - Category 2

Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) - Category 3

Safety data sheet prepared in accordance to the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Pictograms



Signal Word

Danger

Hazardous Statements - Health

H332 - Harmful if inhaled

H304 - May be fatal if swallowed and enters airways

H351 - Suspected of causing cancer

H319 - Causes serious eye irritation

H361 - Suspected of damaging fertility or the unborn child

H315 - Causes skin irritation

H373 - May cause damage to organs through prolonged or repeated exposure

H335 - May cause respiratory irritation

Hazardous Statements - Physical

H226 - Flammable liquid and vapor

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

Precautionary Statements - Prevention

P271 - Use only outdoors or in a well-ventilated area.

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves, protective clothing, eye protection/face protection.

P264 - Wash thoroughly after handling.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment.

P242 - Use only non-sparking tools.

P243 - Take action to prevent static discharges.

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

Precautionary Statements - Response

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 - Call a POISON CENTER/doctor if you feel unwell.

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331 - Do NOT induce vomiting.

P308 + P313 - IF exposed or concerned: Get medical advice/attention.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice/attention.

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P370 + P378 - In case of fire: Use carbon-di oxide, alcohol foam, water spray or dry chemical to extinguish.

P302 + P352 - IF ON SKIN: Wash with plenty of water.

P321 - Specific treatment (see First-Aid on this label).

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

P362 + P364 - Take off contaminated clothing. And wash it before reuse.

P314 - Get Medical advice/attention if you feel unwell.

Precautionary Statements - Storage

P405 - Store locked up.

P403 + P235 - Store in a well-ventilated place. Keep cool.

P403 + P405 - Store in a well-ventilated place. Store locked up.

Precautionary Statements - Disposal

P501 - Dispose of contents/container in accordance with local/national/international regulations.

Hazards Not Otherwise Classified (HNOC)

None.

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	GHS Classifications	% By Weight
0001330-20-7	XYLENE	Acute Tox. Derm. 4, H312; Acute Tox. Inh. 4, H332; Acute Tox. Oral 4, H302; Aquatic Acute 2, H401; Aquatic Chronic 2, H411; Asp. Tox. 1, H304; Carc. 2, H351; Eye Irr. 2A, H319; Flam. Liq. 3, H226; Repr. 1A, H360; Skin Irr. 2, H315; STOT RE 1, H372; STOT SE 3 (Resp.), H335	60% - 85%
0028262-63-7	ACRYLIC RESIN	N.A.	15% - 40%
0000100-41-4	ETHYLBENZENE	Acute Tox. Inh. 4, H332; Acute Tox. Oral 5, H303; Aquatic Acute 2, H401	0% - 5%
0029911-27-1	DIPROPYLENE GLYCOL MONOPROPYL ETHER	N.A.	0% - 5%

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing. If breathing is difficult, trained personnel should administer emergency oxygen if advised to do so by the POISON CENTER/doctor. Get Medical advice/attention if you feel unwell. Eliminate all ignition sources if safe to do so. If exposed/If you feel unwell/If concerned: Call a POISON CENTER/doctor. Take precautions to ensure your own safety (e.g. wear appropriate protective equipment).

Eye Contact

If eye irritation persists: Get medical advice/attention. Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for a duration of 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face.

Skin Contact

Wash with plenty of lukewarm, gently flowing water for a duration of 15-20 minutes or until medical aid is available. If skin irritation occurs or you feel unwell: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Store contaminated clothing under water and wash before re-use or discard. Take off immediately all contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Call a POISON CENTER/doctor if you feel unwell.

Ingestion

Rinse mouth. Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. If vomiting occurs naturally, lie on your side, in the recovery position.

Most important symptoms and effects, both acute and delayed

No data available.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. No specific treatment is required. No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Treat according to symptoms (decontamination, vital functions), no known specific antidote. Treatment should be supportive and based on the judgement of the physician in response to the reaction of the patient.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Small Fire : Dry chemical, foam, carbon dioxide, water-spray or alcohol-resistant foam. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Large Fire : Water spray, fog or alcohol-resistant foam.

Unsuitable Extinguishing Media

Do not use straight stream of water.

Specific Hazards Arising from the Chemical

Fire will produce irritating and toxic gases. Most vapors are heavier than air. Vapors may form explosive mixtures with air Vapors will spread along ground and collect in low or confined areas (sewers, basements, tanks) Vapors may travel to source of ignition and flash back. Many liquids are lighter than water. Containers may explode in fire. May form an ignitable vapor/air mixture in closed tanks or containers.

Precautions for Firefighters

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Cool containers with flooding quantities of water until well after fire is out. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Equipment

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

Stay uphill and/or upstream. Ventilate closed spaces before entering. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing. Evacuate and isolate hazard area and keep unauthorized personnel away. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. A vapor-suppressing foam may be used to reduce vapors.

Protective Equipment

Breathing protection is required. Wear chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA).

Personal Precautions

Do not breathe vapor or mist. Do not get on skin, eyes or clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. Dike far ahead of liquid spill for later disposal.

Methods and Materials for Containment and Cleaning up

Ventilate area after clean-up is complete. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean, non-sparking tools to collect absorbed material.

SECTION 7) HANDLING AND STORAGE

General

Wash hands after use.

Do not breathe vapor or mist.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

All containers must be properly labelled.

Do not get in eyes, on skin, or on clothing.

Eyewash stations and showers should be available in areas where this material is used and stored

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits.

The use of local ventilation is recommended to control emissions near the source.

Report ventilation failures immediately.

Storage Room Requirements

Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored. Keep containers securely sealed when not in use. Containers that have been opened must be carefully resealed to prevent leakage. Indoor storage should meet OSHA standards and appropriate fire codes. Empty containers retain residue and may be dangerous. Store in cool, dry, well-ventilated areas away from heat, direct sunlight and strong oxidizers. Store in approved containers and protect against physical damage. Take precautionary measures against electrostatic discharge. To avoid fire or explosion, dissipate static electricity during transfer by ground and bonding containers and equipment before transferring material.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids.

Skin Protection

Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Use of chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and microorganisms. Examples of preferred glove barrier materials include: Butyl rubber, Polyethylene, Chlorinated polyethylene, Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Viton, Neoprene, Polyvinyl chloride ("PVC" or "vinyl"), Nitrile/butadiene rubber ("nitrile" or "NBR").

Full contact Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 480 min

Material tested: Butoject® (KCL 897 / Aldrich Z677647, Size M).

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 30 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M).

Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 should be followed. Check with respiratory protective equipment suppliers.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

Chemical Name	ACGIH TWA (mg/m3)	ACGIH TWA (ppm)	ACGIH STEL (mg/m3)	ACGIH STEL (ppm)	ACGIH Carcinogen	ACGIH TLV Basis	ACGIH Notations	OSHA TWA (mg/m3)
ETHYLBENZE NE		20			A3	URT & eye irr; ototoxicity; kidney eff; CNS impair	OTO;BEI	435
XYLENE		20				Eye irr & URT irr, hemotologic effects; CNS impair		435

Chemical Name	OSHA TWA (ppm)	OSHA STEL (mg/m3)	OSHA STEL (ppm)	OSHA Carcinogen	OSHA Skin designation	OSHA Tables (Z1, Z2, Z3)	NIOSH TWA (mg/m3)	NIOSH TWA (ppm)
ETHYLBENZE NE	100					1	435	100
XYLENE	100					1	435	100

Chemical Name	NIOSH STEL (mg/m3)	NIOSH STEL (ppm)	NIOSH Carcinogen
ETHYLBENZE NE	545	125	
XYLENE	655	150	

A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans, CNS - Central nervous system, eff - Effects, impair - Impairment, irr - Irritation, URT - Upper respiratory tract

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	7.63 lb/gal
Specific Gravity	N/A
% Solids By Weight	25.00%

Appearance	N/A
Odor Description	N/A
pH	N/A
Water Solubility	N/A
Flammability	Flash point at or above 73°F/23°C and less than 100°F/38°C
Flash Point	80.00 °F
Viscosity	N/A
Lower Explosion Level	N/A
Upper Explosion Level	N/A
Vapor Density	N/A
Freezing Point	N/A
Melting Point	N/A
Low Boiling Point	N/A
Evaporation Rate	N/A
Coefficient Water/Oil	N/A

SECTION 10) STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical Stability

Stable under normal storage and handling conditions.

Possibility of Hazardous Reactions/Polymerization

Will not occur.

Conditions To Avoid

Avoid all possible sources of ignition, heat, sparks, flame, build up of static electricity and contact with incompatible materials.

Incompatible Materials

Strong bases, acids, and oxidizing agents.

Hazardous Decomposition Products

Oxides of carbon.

SECTION 11) TOXICOLOGICAL INFORMATION

Acute Toxicity

Harmful if inhaled

The Acute Toxicity Estimate (ATE) for an oral exposure to this mixture is >5000 mg/kg body weight

The Acute Toxicity Estimate (ATE) for a dermal exposure to this mixture is >5000 mg/kg body weight

The Acute Toxicity Estimate (ATE) for an inhalation (vapour) exposure to this mixture is 14.966 mg/l

Aspiration Hazard

May be fatal if swallowed and enters airways

Carcinogenicity

Suspected of causing cancer

Germ Cell Mutagenicity

Based on available data, the classification criteria are not met.

Respiratory/Skin Sensitization

Based on available data, the classification criteria are not met.

Reproductive Toxicity

Suspected of damaging fertility or the unborn child

Serious Eye Damage/Irritation

Causes serious eye irritation

Skin Corrosion/Irritation

Causes skin irritation

Specific Target Organ Toxicity - Repeated Exposure

May cause damage to organs through prolonged or repeated exposure

Specific Target Organ Toxicity - Single Exposure

May cause respiratory irritation

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Chronic Exposure

0000100-41-4 ETHYLBENZENE

CARCINOGENIC EFFECTS: Ethyl Benzene has been listed by IARC as Group 2B, Possibly Carcinogenic to Humans.

TERATOGENIC EFFECTS: Ethyl Benzene has been Classified as POSSIBLE for humans.

0001330-20-7 XYLENE

High exposure to Xylenes in some animal studies have been reported to cause health effects on the developing embryo/fetus.

Xylene in high concentrations has caused embryotoxic effects in laboratory animals.

Potential Health Effects - Miscellaneous

0000100-41-4 ETHYLBENZENE

Is an IARC, NTP or OSHA carcinogen. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. Studies in laboratory animals have shown reproductive, embryotoxic and developmental effects. WARNING: This chemical is known to the State of California to cause cancer.

0001330-20-7 XYLENE

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: bone marrow, cardiovascular system, central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. High exposures may produce irregular heart beats. Canada classifies Xylene as a developmental toxin as high exposures to xylenes in some animal studies have been reported to cause health effects on the developing fetus/embryo. These effects were often at levels toxic to the adult animal. The significance of these effects to humans is not known. Repeated or prolonged skin contact may cause any of the following: irritation, dryness, cracking of the skin.

0001330-20-7 XYLENE

LC50 (rat): 6350 ppm (4-hour exposure) (unspecified isomers and ethylbenzene) (1) LC50 (rat): 6700 ppm (4-hour exposure) (65% m-xylene, 7.6% o-xylene, 7.8% p-xylene, 19.3% ethylbenzene) (2) ethylbenzene) (1)

LC50 (rat): 6700 ppm (4-hour exposure) (65% m-xylene, 7.6% o-xylene, 7.8% p-xylene, 19.3% ethylbenzene) (2)

LD50 (oral, rat): 5400 mg/kg (52% m-, 19% o-, 24% p-) (1) LD50 (oral, female mouse): 5251 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)

LD50 (oral, male mouse): 5627 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)

LD50 (dermal, rabbit): 12180 mg/kg (m-xylene); greater than 1700 mg/kg (mixed xylenes - undefined composition) (3)

LD50 (oral, female mouse): 5251 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)

LD50 (oral, male mouse): 5627 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)

LD50 (dermal, rabbit): 12180 mg/kg (m-xylene); greater than 1700 mg/kg (mixed xylenes - undefined composition) (3)

0000100-41-4 ETHYLBENZENE

LC50 (inhalation, rat): 4000 ppm; 4-hour exposure (3)

LD50 (oral, rat): 3.5 g/kg (1,3,5,10)

LD50 (oral, rat): 4.72 g/kg (3,5,7,8)

LD50 (dermal, rabbit): 17.8 g/kg (11)

SECTION 12) ECOLOGICAL INFORMATION

Ecotoxicity

Based on available data, the classification criteria are not met.

Persistence and Degradability

0001330-20-7 XYLENE

50% of applied radiolabelled o-xylene was mineralised in 23 days, and 50% p-xylene was mineralised in 13 days.

Bioaccumulative Potential

No data available.

Mobility in Soil

No data available.

Other Adverse Effects

No data available.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

It is the responsibility of the user of the product to determine at the time of disposal whether the product meets local criteria for hazardous waste. Waste management should be in full compliance with national, state and local laws. Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes.

SECTION 14) TRANSPORT INFORMATION

	U.S. DOT Information	IMDG Information	IATA Information
UN Number:	UN1268	UN1268	UN1268
UN proper shipping name:	Petroleum distillates, n.o.s.	Petroleum distillates, n.o.s.	Petroleum distillates, n.o.s.
Transport Hazard class(es)	3	3	3
Packing group	III	III	III
Hazardous substance (RQ)	No Data Available	No Data Available	No Data Available
Environmental hazards	No Data Available	No Data Available	No Data Available
Special precautions for user	No Data Available	No Data Available	No Data Available
Transport in bulk according to Annex II of MARPOL and the IBC code	No Data Available	No Data Available	No Data Available

SECTION 15) REGULATORY INFORMATION

Safety, health and environmental regulations

The product has been evaluated against the following relevant regulations: U.S.A Toxic Substance Control Act (TSCA) California Proposition 65 Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312 Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313 Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA)



WARNING: This product can expose you to chemicals including ETHYLBENZENE, which is [are] known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

CAS	Chemical Name	% By Weight	Regulation List
0001330-20-7	XYLENE	60.00% - 85.00%	SARA313, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, SARA312, TSCA - Toxic Substances Control Act (TSCA)
0028262-63-7	ACRYLIC RESIN	15.00% - 40.00%	SARA312, TSCA - Toxic Substances Control Act (TSCA)
0000100-41-4	ETHYLBENZENE	0.00% - 5.00%	SARA313, CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act, SARA312, TSCA - Toxic Substances Control Act (TSCA), CA_Prop65 - California Proposition 65, CA_Prop65_Type_Toxicity_Cancer - CA_Proposition65_Type_Toxicity_Cancer
0029911-27-1	DIPROPYLENE GLYCOL MONOPROPYL ETHER	0.00% - 5.00%	SARA312, TSCA - Toxic Substances Control Act (TSCA)

SECTION 16) OTHER INFORMATION

Glossary

ACGIH - American Conference of Governmental Industrial Hygienists; CAS - Chemical Abstracts Service ; Chemtrec - Chemical Transportation Emergency Center; DSL - Domestic Substances List; ESL - Effects screening levels; GHS - "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations; HMIS - Hazardous Material Information Service; IATA - Dangerous Goods Regulations (DGR) for the air transport (IATA); IMDG - International Maritime Dangerous Goods Code; LC - Lethal Concentration; LD - Lethal Dose; NFPA - National Fire Protection Association; OEL - Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL - Permissible Exposure Limit; SARA 313 - Superfund Amendments and Reauthorization Act, Section 313; SCBA - Self Contained Breathing Apparatus; ppm - parts per million; STEL - Short-term exposure limit; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act Public Law 94-469; TWA - Time-weighted average; US DOT- US Department of Transportation.

Version 2.0:

Revision Date: Apr 11, 2024

Full text of H-Statements referred to under Section 3

- H372 Causes damage to organs through prolonged or repeated exposure.
- H319 Causes serious eye irritation
- H315 Causes skin irritation
- H226 Flammable liquid and vapor
- H332 Harmful if inhaled
- H302 Harmful if swallowed
- H312 Harmful in contact with skin
- H304 May be fatal if swallowed and enters airways
- H303 May be harmful if swallowed
- H335 May cause respiratory irritation
- H360 May damage fertility or the unborn child
- H351 Suspected of causing cancer
- H401 Toxic to aquatic life
- H411 Toxic to aquatic life with long lasting effects

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.