



TENON[®]

Concrete & Masonry Sealer WB



Protects & seals

Tenon[®] Concrete & Masonry Sealer WB is a water-based sealer that penetrates and reacts chemically within the capillaries of the concrete or masonry, bonding to the silica in the substrate to protect against moisture penetration, water-related staining, atmospheric chemicals, and deterioration. It is used to protect and seal clean, dry, coating-free, fully cured concrete, brick masonry, concrete masonry units, stucco, stone terrazzo, architectural concrete, and some natural stones.

Features:

- Repels water
- Dries tack-free
- Natural-looking invisible protection
- Non-staining, colorless, & non-yellowing
- Ready-to-use (no mixing, do not dilute)
- High alkali resistance
- Breathable, does not trap moisture
- Deep-penetrating & long-lasting
- Easy to apply with sprayer or roller
- Low volatility, solvent-free
- Protects from effects of rain & other water penetration, chemicals, deicing salts, freeze-thaw, & smog
- Reduces efflorescence



TENON®

Concrete & Masonry Sealer WB



Application

1. Apply with low-pressure sprayer with a wet-fan type spray nozzle, power roller with 1" nap, or brush.
2. On vertical surfaces, apply using a flooding application from the bottom up. Apply evenly and sufficiently to wet the substrate completely with a minimum 6 - 8 in. (5 cm) run-down below the spray pattern.
3. On horizontal surfaces, the liquid sealer should pond on the surface for at least 5 seconds before being absorbed. Roll out any pools that accumulate on the surface after 5 minutes. If any dry areas form before 5 minutes, apply an additional light coat to those dry areas.
4. It is important to spray or roll the surface to evenly spread the sealer. Surface should have a uniform wet-look until the sealer dries.
5. Very porous surfaces may require 2 coats of Concrete & Masonry Sealer WB, wet on wet application. It is better to apply 2 thin coats than 1 heavy coat.
6. When applying to split-face block, be sure the block is dry to allow for good penetration with no run-down. If applied to damp block, the water on the surface may prevent proper penetration, which may prevent it from achieving a natural look.

Available In:

Tenon® Concrete & Masonry Sealer WB is available in a 1 gal. (3.78 L) bottle and a 5 gal. (18.93 L) pail.



1 Gal.

BOM #120673



5 Gal.

BOM #120674

For professional use only.

It is the responsibility of the installer/applicator to ensure the suitability of the product for its intended use. For technical assistance, please contact TCC Materials. To acquire technical and safety literature, please visit our website.



TCC Materials
2025 Centre Pointe Blvd
Mendota Heights, MN 55120

Phone: 651.688.9116
Email: info@tccmaterials.com
Web: tccmaterials.com